

**WHEN MBS FIGURES ARE SPECIFIED ON THE EQUIPMENT
THE SAFETY FACTOR YOU CHOOSE TO APPLY TO A RECOVERY SITUATION AND ITS MAX LOAD
WILL DICTATE WHAT MBS WILL BE NEEDED BY THE EQUIPMENT**

<p>EXAMPLE 1: 3000KG OBJECT BEING RECOVERED SAFETY FACTOR OF 2 APPLIED SOFT SHACKLE NEEDS TO BE RATED 6,000KG / 6T OR ABOVE SNATCH RING OR RECOVERY RING NEEDS TO BE RATED AT 6,00kg / 6t / 5.88kN OR ABOVE</p>	<p>EXAMPLE 2: 2500KG OBJECT BEING RECOVERED SAFETY FACTOR OF 3 APPLIED SOFT SHACKLE NEEDS TO BE RATED 7,500KG / 7.5T OR ABOVE SNATCH RING OR RECOVERY RING NEEDS TO BE RATED AT 7,500kg / 7.5t / 73.6kN OR ABOVE</p>	<p>EXAMPLE 3: 3000KG OBJECT BEING RECOVERED SAFETY FACTOR OF 5 APPLIED SOFT SHACKLE NEEDS TO BE RATED 15,000KG / 15T OR ABOVE SNATCH RING OR RECOVERY RING NEEDS TO BE RATED AT 15,000kg / 15t / 147.1kN OR ABOVE</p>
--	---	--

